



MWM-7C1



MWM-7C1/P

## PANEL MICROPHONE MWM-7C1/MWM-7C1/P

PRODUCT CODE 51158, 51157

### FEATURES

- Surface mounted microphone with balanced, line level output
- Used for recording audio, covert monitoring, audio input for CCTV cameras
- Two options available: stainless panel with activate button or Clipsal wall plate
- LED indicator for activity feedback

### OPTIONAL ACCOMPANYING PRODUCTS

- Audio Monitoring Device (UAI-AMD)
- Power Supply Unit (PSU-242)

### SPECIFICATIONS

<b>Microphone</b>	160 Hz – 16 kHz (input circuit frequency response $\pm 3$ dB)
<b>Output Level</b>	-4 dBu nominal
<b>Output Impedance</b>	600 $\Omega$
<b>Control Buttons</b>	1 x stainless steel mechanical configurable PTT or toggle on/off
<b>Auxiliary Functions</b>	Relay contacts (1 x NO/NC) max. 2 A @ 24 V d.c.
<b>Power Input</b>	(12 – 32) V d.c., 24 V d.c. nominal
<b>Power Consumption</b>	1.8 W max. @ 24 V d.c. (MWM-7C1) 0.9 W max. @ 12 V d.c. (MWM-7C1/P)
<b>Operating Temperature</b>	(0 - 50) °C
<b>Operating Humidity</b>	(10 – 90) % RH (non-condensing)
<b>Indicators</b>	Green indicator (MWM-7C1)
<b>Cabling</b>	Audio: single screened pair cable Power: 0.75 mm <sup>2</sup> , multi-strand (max. 100 m)
<b>Connectors</b>	Power: 2 way 3.81 mm pluggable screw terminal block Signal: 8 way 3.81 mm pluggable screw terminal block
<b>Form Factor</b>	Flush wall panel
<b>Dimensions (WxHxD)</b>	116 mm x 70 mm x 50 mm
<b>Weight</b>	0.25 kg (MWM-7C1) 0.2 kg (MWM-7C1/P)
<b>Material</b>	Stainless steel (MWM-7C1) Plastic, white (MWM-7C1/P)
<b>Finishes</b>	Linish (MWM-7C1) Clipsal single gang plate (MWM-7C1/P)
<b>Environment</b>	Indoor use only
<b>Vandal Resistant</b>	Yes (MWM-7C1 only)
<b>Mounting Options</b>	Flush mount direct into ceiling or wall (MWM-7C1), mounting hole pitch suits single gang electrical plate (MWM-7C1/P)
<b>Fixings</b>	M3.5, M4 or self tapping screws (MWM-7C1) M3.5 screws (MWM-7C1/P) (included with purchase)