



VMS-750

VMS-750
JHS-1

MONITOR STATION VMS-750 (OPTIONAL JHS-1)

PRODUCT CODE 51336, 51432

FEATURES

- Text message facility from concierge/building manager*
- Caller snapshot image taken, and made visible on monitor station, when call is unanswered from entrance station
- View CCTV footage on monitor station*
- Duress calling to concierge/control room/building manager*
- Privacy enable/disable feature to mute calling
- Home automation control from monitor station (using C-Bus)*
- Intercommunication between apartments*
- Easy to use, 7" intuitive touchscreen design
- Power saving mode while unit not in use

OPTIONS

- Ergonomic handset - black only (JHS-1)
- Customisable GUI

SPECIFICATIONS

Screen	7" TFT colour LCD, 16:9 aspect ratio Active area: 152 mm x 91 mm Resolution 800 x 480, 18-bit RGB LED backlight (white) Contrast ratio: 400 Brightness: 300 cd/m ² Viewing angle: 120° V, 140° H
Speaker	2 x 8 Ω 2 W
Speaker Amplifier	50 Hz – 7 kHz (output circuit frequency response -3 dB), 2.5 W
Max. Acoustic Output	88 dB SPL @ 1 m, 0 dBFS 1 kHz (non-clipped) sine wave signal
Microphone	Electret condenser, omnidirectional, sensitivity -56 dB 50 Hz – 7 kHz (input circuit frequency response ±3 dB mic)
Audio Streaming Bandwidth	256 kb/s both ways
Control Buttons	Unlimited* soft buttons, fully customisable GUI control
Auxiliary Functions	Relay contacts (1 x NO/NC), light sensor, privacy mode
Power Input	IEEE 802.3af Power over Ethernet (PoE) Auxiliary power input: (12 - 32) V d.c.
Power Consumption	10 W max. (2.5 W standby)
Operating Temperature	(0 - 50) °C
Operating Humidity	(20 - 90) % relative humidity (non-condensing)
Cabling	LAN: 4 pair UTP CAT-5/6, multi-strand, 24 AWG, max. 100 m Power: Figure 8, 0.75 mm ² conductors
Dimensions (WxHxD)	280 mm x 172 mm x 33 mm (VMS-750) 340 mm x 172 mm x 64 mm (incl. JHS-1)
Weight	1.2 kg (VMS-750) 1.5 kg (incl. JHS-1)
Material	Plated zinc, acrylic, ABS, zinc plated steel chassis
Finishes	Satin chrome surround, black acrylic screen bezel
Environment	Indoor use only
Mounting Options	Wall mount kit (WMK-1) (included), surface mount backbox (SWE-13/SWE-14), desk mount kit (DMS-1/DMS-2)
Fixings	Clips to mounting options and retained with 1 x M3 CSK screw

*Dependent on server configuration and network bandwidth