



IPM-360



IPM-360H



IPM-360G



IPM-360GH

IP MASTER INTERCOM STATION IPM-360/360H/360G/360GH

PRODUCT CODE 51516, 51533, 51534, 51535

FEATURES

- Network communications are based around TCP/IP protocol suite
- Static or dynamic IP address assignment. Dynamic Host Configuration Protocol (DHCP) is supported
- IEEE 802.3af PoE support
- Backlit display for reliable viewing in dark conditions

OPTIONAL ACCOMPANYING PRODUCTS

- Handset (IPM-360H/IPM-360GH)
- Flexible gooseneck microphone (IPM-360G/IPM-360GH)
- Headset (AU144)

SPECIFICATIONS

Screen	2 x 16 characters LCD, blue background with white text
Speaker	2 x 8 Ω, 2 W RMS (power rating)
Speaker Amplifier	200 Hz – 7.1 kHz (output circuit frequency response -3 dB)
Max. Acoustic Output	84 dB SPL @ 1 m (3.2 ft) 0 dBFS 1 kHz (non-clipped) sine wave signal
Output Distortions	0.2% (0.5 W RMS speaker output)
Microphone	Internal Omni-Directional Electret (IPM-360, IPM-360H) Uni-Directional Flexible Gooseneck (IPM-360G, IPM-360GH)
Audio Streaming Bandwidth	256 kb/s both ways
Control Buttons	Metal, vandal resistant, alphanumeric keypad and PTT switch
Auxiliary Functions	Relay contacts (1 x NO)
Power Input	(12 - 32) V d.c. or IEEE 802.3af Power over Ethernet (PoE)
Power Consumption	7 W max. (3.6 W standby)
Operating Temperature	(0 - 50)°C (32 - 122)°F
Operating Humidity	(10 - 95) % relative humidity (non-condensing)
Cabling	4 pair UTP CAT-5/5e/6, multi-strand (0.2 mm ² / 0.00031 in ²), 100 m (328.08 ft) max.
Dimensions (WxHxD)	193 mm x 103 mm x 236 mm (7.6 in x 4.05 in x 9.3 in) IPM-360/IPM-360G 254 mm x 110 mm x 236 mm (10 in x 4.3 in x 9.3 in) IPM-360H/IPM-360GH
Weight	2.1 kg (4.6 lb) IPM-360 2.5 kg (5.5 lb) IPM-360H 2.3 kg (5.1 lb) IPM-360G 2.7 kg (5.9 lb) IPM-360GH
Material	Face plate: satin chrome plated mild steel Base: powder coated mild steel Window: gloss acrylic
Environment	Indoor use only
Mounting Options	Desk mount only