

# ACCESSORIES

MWM-7C1 | 51158



## Features

- Surface mounted microphone with balanced, line level output
- Used for recording audio, covert monitoring, audio input for CCTV cameras
- Two options available: stainless panel with activate button or Clipsal wall plate
- LED indicator for activity feedback

## Optional Accompanying Products

- Power Supply Unity (PSU-242)

## Specifications

|                       |   |
|-----------------------|---|
| Microphone            | 160 Hz – 16 kHz (input circuit frequency response $\pm 3$ dB)   |
| Output Level          | -4 dBu nominal  |
| Output Impedance      | 600 $\Omega$  |
| Control Buttons       | 1 x stainless steel mechanical configurable PTT or toggle on/off  |
| Auxiliary Functions   | Relay contacts (1 x NO/NC) max. 2 A @ 24 V d.c.   |
| Power Input           | (12 – 32) V d.c., 24 V d.c. nominal   |
| Power Consumption     | 1.8 W max. @ 24 V d.c.  |
| Operating Temperature | (0 - 50) °C (32 - 122) °F   |
| Operating Humidity    | (10 – 90) % RH non-condensing   |
| Indicators            | Green indicator   |
| Cabling               | Audio: single screened pair cable<br>Power: 0.75 mm <sup>2</sup> (0.0011 in <sup>2</sup> ), multi-strand 100 m (328 ft) max.    |
| Connectors            | Power: 2 way 3.81 mm (0.15 in) pluggable screw terminal block<br>Signal: 8 way 3.81 mm (0.15 in) pluggable screw terminal block |
| Form Factor           | Flush wall panel  |
| Dimensions (WxHxD)    | 116 mm x 70 mm x 50 mm (4.5 in x 3 in x 2 in)   |
| Weight                | 0.25 kg (1.55 lb)   |
| Material              | 316 stainless steel (2 mm / 0.08 in)  |
| Finish                | Linish  |
| Environment           | Indoor use only   |
| Mounting Options      | Flush mount direct into ceiling or wall   |
| Fixings               | M3.5, M4 or self tapping screws   |

# ACCESSORIES

MWM-7C1/P | 51157



## Features

- Surface mounted microphone with balanced, line level output
- Used for recording audio, covert monitoring, audio input for CCTV cameras
- Clipsal wall plate option

## Optional Accompanying Products

- Power Supply Unity (PSU-242)

## Specifications

|                       |   |
|-----------------------|---|
| Microphone            | 160 Hz – 16 kHz (input circuit frequency response ±3 dB)  |
| Output Level          | -4 dBu nominal  |
| Output Impedance      | 600 Ω   |
| Auxiliary Functions   | Relay contacts (1 x NO/NC) max. 2 A @ 24 V d.c.   |
| Power Input           | (12 – 32) V d.c., 24 V d.c. nominal   |
| Power Consumption     | 0.9 W max. @ 12 V d.c.  |
| Operating Temperature | (0 - 50) °C (32 - 122) °F   |
| Operating Humidity    | (10 – 90) % RH non-condensing   |
| Cabling               | Audio: single screened pair cable<br>Power: 0.75 mm² (0.0011 in²), multi-strand 100 m (328 ft) max.                             |
| Connectors            | Power: 2 way 3.81 mm (0.15 in) pluggable screw terminal block<br>Signal: 8 way 3.81 mm (0.15 in) pluggable screw terminal block |
| Form Factor           | Flush wall panel  |
| Dimensions (WxHxD)    | 116 mm x 70 mm x 50 mm (4.5 in x 3 in x 2 in)   |
| Weight                | 0.2 kg (0.44 lb)  |
| Material              | Plastic, white  |
| Finish                | Clipsal single gang plate   |
| Environment           | Indoor use only   |
| Mounting Options      | Mounting hole pitch suits single gang electrical plate  |
| Fixings               | M3.5 screws (included with purchase)  |