



VMI-155M

VMI STANDALONE MASTER STATION VMI-155M

PRODUCT CODE 50634

FEATURES

- Standalone intercom system
- Master station supports up to 4 slave intercoms
- Balanced line out for recording
- Vandal resistant design
- Dry relay contact output for door/gate control

CUSTOMISATION

- Intercom face etching

SPECIFICATIONS

Speaker	4 Ω, 3 W RMS (power rating)
Speaker Amplifier	60 Hz to 12 kHz, 1 W RMS
Max. Acoustic Output	88 dB SPL @ 1 m (3.28 ft), 1 kHz (non-clipped) sine wave signal
Speaker Hole Size	42 holes x 4 – 7 mm (0.15 - 0.28 in) diameter
Microphone	Electret condenser, omnidirectional, sensitivity -55 dB 160 Hz – 16 kHz (input circuit frequency response ±3 dB)
Microphone Hole Size	2.5 mm (0.01 in) diameter
Audio Bandwidth	160 Hz - 12 kHz
Control Buttons	4 x stainless steel call push buttons, 19 mm (0.75 in) 1 x stainless steel push-to-talk button, 19 mm (0.75 in)
Auxiliary Functions	Electronically balanced signal, -4 dBu nominal
Power Input	(12 – 32) V d.c. (24 V nominal)
Power Consumption	5 W max.
Operating Temperature	(0 – 50)°C (32 – 122)°F
Operating Humidity	(10 – 95) % relative humidity (non-condensing)
Cabling	Audio & Data: UTP CAT-5/6, multi-strand, 24 AWG Recording Audio: single pair screened cable Power: Figure 8, 0.75 mm ² (0.0011 in ²) multi-strand
Configuration	1-4 Jacques VSL-251 intercom terminals (daisy chained)
Dimensions (WxHxD)	130 mm x 290 mm x 45 mm (5.12 in x 11.42 in x 1.77 in)
Weight	1.0 kg (2.20 lb)
Material	316 stainless steel (2 mm / 0.08 in)
Finishes	Linish
Environment	Indoor and outdoor
Vandal Resistant	Yes
Mounting Options	Flush mount backbox (FWE-1), surface mount backbox (SWE-1/SWE-9SS)
Mounting Holes	6 holes x 5 mm (0.19 in) diameter
Fixings	6 x M4 security torx screws