



*The NCV system  
allows prison visitors  
to clearly communicate  
with individual inmates  
while preventing  
physical contact.*



NCV IP HANDSET VSL-341H

PRODUCT CODE 52128

FEATURES

Robust vandal resistant handset with armoured cord and anchoring

SPECIFICATIONS

Speaker (earpiece)	1 x 130 Ω
Speaker Amplifier	50 Hz – 7 kHz (output circuit frequency response -3 dB), 2.5 W
Max. Acoustic Output	115 dB SPL with closed ear coupling 1 kHz full scale sine wave and default gain settings
Microphone (mouthpiece)	1 x 130 Ω dynamic
Power Input	(12-36) V d.c JPoE (24 v.d.c.) via optional JPP-6/12/240 - PoEA-1/6
Power Consumption	1.8 W max. (1.6 W standby) PoE Class 2 (3.84-6.49) W
Operating Temperature	(0 – 55)°C (32 – 122)°F
Operating Humidity	(10 – 95) % relative humidity (non-condensing)
Cabling	4 pair UTP CAT-5/6, multi-strand, 24 AWG, 100 m (328 ft) max.
Dimensions (WxHxD)	130 mm x 290 mm x 58 mm (5.12 in x 11.42 in x 2.28 in) (depth excludes handset, cord and cradle)
Weight	1.55 kg (3.42 lb)
Material	316 stainless steel panel (2 mm / 0.08 in)
Finishes	Linish
Environment	Indoor
Vandal Resistant	Yes
Mounting Options	Flush mount backbox (FWE-1), surface mount backbox (SWE-1)
Mounting Holes	8 holes x 5.5 mm (0.22 in) diameter
Fixings	8 x M4 security torx screws