



INTERCOM TERMINAL VSL-351+

PRODUCT CODE 51612

FEATURES

- IP audio intercom terminal
- Standard PoE powered (IEEE 802.3af)
- Two configurable relays that can control lights, gate/door access etc.
- Tamper detection and attempted device removal notification
- Automated testing of speaker and microphone
- Single call button
- Water and vandal resistant

CUSTOMISATION

- Call button colour
- Call instruction etching

SPECIFICATIONS

Speaker	1 x 4 Ω, 1 W RMS (power rating)
Speaker Amplifier	50Hz - 7kHz (output circuit frequency response -3 dB), 2.5 W
Max. Acoustic Output	88 dB SPL @ 1 m, 0 dBFS 1 kHz (non-clipped) sine wave signal
Speaker Hole Size	42 x 4 – 7 mm Ø holes
Microphone	Electret condenser, omnidirectional, sensitivity -56 dB 50Hz - 7 kHz (input circuit frequency response ±3 dB mic)
Microphone Hole Size	1 x 2.5 mm Ø hole
Audio Streaming Bandwidth	128 kb/s one way, 256 kb/s both ways
Control Buttons	1 x piezo switch, red, 19 mm
Auxiliary Functions	Relay contacts (2 x NO/NC), 30 V d.c./2 A Tamper detection and attempted device removal notification Automated testing of speaker and microphone
Power Input	IEEE 802.3af Power over Ethernet (PoE) (cannot be locally powered)
Power Consumption	4.5 W max. (1.6 W standby) PoE Class 2 (3.84-6.49) W
Operating Temperature	(0 - 55) °C
Operating Humidity	(10 - 95) % relative humidity (non-condensing)
Cabling	4 pair UTP CAT-5/6, multi-strand, 24 AWG, max. 100 m
Dimensions (WxHxD)	125 mm x 180 mm x 58 mm 67 mm min. mounted depth
Weight	0.59 kg
Material	304 stainless steel (2 mm)
Finishes	Linish
Environment	Indoor
Vandal Resistant	Yes; strong front panel, speaker and microphone aperture vandal protected
Mounting Options	Flush mount backbox (FWE-14), surface mount backbox (SWE-6/SWE-4SS), rainhood (SRH-1)
Mounting Holes	4 x 4.5 mm Ø screw holes
Fixings	4 x M4 security torx screws (included with purchase of backbox)