



INTERCOM TERMINAL VSL-371W+

PRODUCT CODE 51672

FEATURES

IP audio intercom terminal, narrow design suitable for mounting in gate posts and doorways
 Standard PoE powered (IEEE 802.3af)
 Two configurable relays that can control lights, gate/door access etc.
 Tamper detection and attempted device removal notification
 Automated testing of speaker and microphone
 Marine grade 316 stainless steel face plate
 Microphone aperture deters insect nesting and water beads
 Water and vandal resistant

CUSTOMISATION

Call button colour
 Call instruction etching

SPECIFICATIONS

| | |
|----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Speaker | 1 x 4 Ω, 3 W RMS (power rating) |
| Speaker Amplifier | 50 Hz - 7 kHz (output circuit frequency response -3dB), 2.5 W |
| Max. Acoustic Output | 85 dB SPL @ 1 m, 0 dBFS 1 kHz (non-clipped) sine wave signal |
| Speaker Hole Size | 58 x 3 – 6 mm Ø holes |
| Microphone | Electret condenser, omnidirectional, sensitivity -56 dB 50 Hz - 7 kHz (input circuit frequency response ±3 dB mic) |
| Microphone Hole Size | 1 x "koala nose", 6 x 10 mm |
| Audio Streaming Bandwidth | 128 kb/s one way, 256 kb/s both ways |
| Control Buttons | 1 x piezo switch, red, 19 mm |
| Auxiliary Functions | Relay contacts (2 x NO/NC), 30 V d.c./2 A Tamper detection and attempted device removal notification Automated testing of speaker and microphone |
| Power Input | IEEE 802.3af Power over Ethernet (PoE) (cannot be locally powered) |
| Power Consumption | 4.5 W max. (1.6 W standby) PoE Class 2 (3.84-6.49) W |
| Operating Temperature | (0 - 55) °C |
| Operating Humidity | (10 - 95) % relative humidity (non-condensing) |
| Cabling | 4 pair UTP CAT-5/6, multi-strand, 24 AWG, max. 100 m |
| Dimensions (WxHxD) | 75 mm x 261 mm x 92 mm 95 mm min. mounted depth |
| Weight | 0.65 kg |
| Material | 316 stainless steel (2 mm) |
| Finishes | Linish |
| Environment | Indoor and outdoor |
| Vandal Resistant | Yes; strong front panel, speaker and microphone aperture vandal protected |
| Mounting Options | Flush mount (cut out and tap), rainhood (SRH-4) |
| Mounting Holes | 6 x 5 mm Ø screw holes |
| Fixings | 6 x M4 security torx screws (included with purchase of backbox) |