



## EXCHANGE LINE INTERFACE ELI-3B1

PRODUCT CODE 51124

### FEATURES

- An embedded device allowing for intercom calling to 3rd party PSTN/PABX networks
- Originate and receive calls from intercom devices to/from external PSTN/PABX devices
- PoE support; power, data and digital voice communications require only a single CAT-5 cable
- Bi- directional DTMF supported
- Full DTMF support (including hook-flash) for enhanced PABX support
- Two relay outputs with change over contacts
- Terminal for ground connection
- LED indicators for troubleshooting
- Flexible mounting options (shelf, wall, DIN rail)
- Integrates PABX/PSTN with 650 series system

### SPECIFICATIONS

<b>Output Level to Tel. Line</b>	-10 dB nominal
<b>Frequency Response</b>	300 Hz - 3.6 kHz (-3 dB)
<b>Output and Input Distortion</b>	< -40 dB
<b>Power Input</b>	(12 - 32) V d.c.
<b>Power Consumption</b>	3.6 W
<b>Protocols Supported</b>	TCP/IP: UDP, DHCP, RTP, RTCP, JCCP
<b>Dimensions (WxHxD)</b>	103 mm x 53 mm x 168 mm (excluding connectors and fixing brackets)
<b>Weight</b>	0.5 kg
<b>Material</b>	Extruded aluminium
<b>Finishes</b>	Anodised, black
<b>Environment</b>	Indoor use only
<b>Mounting Options</b>	DIN rail mount, shelf or wall

### ELI-3B1 DIAGRAM

