



INTERCOM TERMINAL VSL-74K

PRODUCT CODE 51459

FEATURES

- IP device used for voice control and communications
- 12 button keypad
- Standard PoE powered (IEE 802.3af)
- Marine grade 316 type stainless steel face place
- Two configurable dry contact relays (control lights, gate/door access)
- Water bead and insect nest deterring microphone aperture
- Vandal resistant stainless steel front panel with call instruction etching

SPECIFICATIONS

Microphone	Electret condenser, omnidirectional, sensitivity -56 dB
Speaker	1 x 4Ω, 1W RMS (power rating)
Speaker Amplifier	50Hz - 7kHz (output circuit frequency response -3dB), 2.5 W
Configuration	Unlimited* number of VSL-74K
Control Buttons	12 button keypad (0-9, * and #)
Dimensions (WxHxD)	130mm x 290mm x 53mm
Weight	1.4kg
Environment	Internal and external use
Material	316 stainless steel front panel
Finishes	Linished and bead blasted
Vandal Resistant	Yes
Mounting Options	Flush mount backbox (FWE-1), surface mount backbox - powder coated (SWE-1) or stainless steel (SWE-9SS)
Fixings	6 x M4 security torx screws
Power Input	IEEE.802.3af Power over Ethernet (PoE) Auxiliary power input: (12 - 32) V d.c.
Power Consumption	8.5 W max (2.0 W standby)
Cabling: Power & Ethernet	4 pair UTP CAT-5/6, multi-strand, 24 AWG - max 100m
Audio Streaming Bandwidth	200 Hz - 7 kHz +/- 3 dB (voice)
Max. Acoustic Output	88 dB SPL @ 1m, 0dBFS 1kHz (non-clipped) sine wave signal
Auxiliary Functions	Relay contacts (2 x NO/NC)
Operating Temperature	0 - 50°C
Operating Humidity	20 - 90% relative humidity (non-condensing)

*Dependent on server configuration and network bandwidth