

EMERGENCY AND EVACUATION PANEL

Flush

PRODUCT CODE VARIOUS

FEATURES

Evacuation and lockdown push buttons
Stainless steel vandal resistant panel - various sizes
Custom etching available
Configurable buttons

0.45 kg (2 buttons installed) upto 0.90 kg (4 buttons installed)

REQUIRED PRODUCTS

Adam Relay Module 6060

Mounting Options

Weight

PANEL SPECIFICATIONS GENERAL

	0.40 Ng (2 b)		, .	3 (
Form Factor	Flush wall panel					
Dimensions (WxHxD)	See over (note: buttons protrude 25.5 mm from front of panel)					
Material	304 Stainless Steel 2 mm					
Finishes	Linish					
Environment	Indoor use only					
SPECIFICATIONS (PER BUT	TON)					
No. of Contacts	2					
IP Rating	IP40					
Contact Arrangement	1 X NO 1 X NC					
Rated Insulation Voltage	500 V					
Operational Voltage and Cur	rent Ratings					
Rated Voltage	24 V	48 V	110 V	220 V	380 V	500 V
Direct Current	10 A	5 A	2.2 A	1.1 A		
Alternating Current (P.F. = 0.7)			10 A	6 A	4 A	2 A
Contact Resistance	≤ 50 mΩ					
Insulation Resistance	≥ 100 MΩ					
Dielectric Strength	3000 V a.c. 50 Hz					
Vibration Resistance	50 Hz, Amp	50 Hz, Amplitude 1.0 mm p-p				
Shock Resistance	≥ 10 g	≥ 10 g				
Lifetime		Mechanical: ≥ 200,000 times Electrical: ≥ 50,000 times				
Terminal	Screw clam	Screw clamp, accepts 2×1.5 mm dia. wires max				
Operating Force	800-2200 g	800-2200 g				
Weight	55 g					
Dimensions (W x H x D)	40 mm x 37	mm x 78 mn	n			
Material	Plastic body	, metal electi	rical contacts			
Environment	Indoor use of	only				
Operating Temperature	(-25 - +55)°(С				
Operating Humidity	45% - 85%	RH (non-con	densing)			
Compliance	IEC60947-5	: 1				

www | jacques.com.au 1 of 3

ADDITIONAL CONFIGURATIONS



PBP-052/C0

PRODUCT CODE 51894

Weight	0.45 kg (2 buttons installed)	
Dimensions (WxHxD)	125 mm x 180 mm (buttons protrude 25.5 mm from front of panel)	
Orientation	Vertical	
Buttons	2 red, mushroom push-lock, turn-reset switches	
Etching	Fire Evacuation Emergency Lockdown Customised etching available	



PBP-044/C2

PRODUCT CODE 51918

Weight	0.90 kg (4 buttons installed)	
Dimensions (WxHxD)	130 mm x 290 mm (buttons protrude 25.5 mm from front of panel)	
Orientation	Vertical	
Buttons	3 red + 1 green, mushroom push-lock, turn-reset switches	
Etching	No panel etching Customised etching available	



PBP-044/C3

PRODUCT CODE 51921

Weight	0.90 kg (4 buttons installed)	
Dimensions (WxHxD)	130 mm x 290 mm (buttons protrude 25.5 mm from front of panel)	
Orientation	Vertical	
Buttons	4 red, mushroom push-lock, turn-reset switches	
Etching	No panel etching	
	Customised etching available	



PBP-044/C4

PRODUCT CODE 51925

0.90 kg (4 buttons installed)	
130 mm x 290 mm (buttons protrude 25.5 mm from front of panel)	
Vertical	
3 red mushroom push-lock, turn-reset switches 1 green mustroom momentary switch	
No panel etching Customised etching available	



PBP-044/C0

PRODUCT CODE 51896


Weight	0.90 kg (4 buttons installed)	
Dimensions (WxHxD)	290 mm x 130 mm (buttons protrude 25.5 mm from front of panel)	
Orientation	Horizontal	
Buttons	4 red, mushroom push-lock, turn-reset switches	
Etching	Student Call Fire Evacuation Duress Emergency Lockdown	
	Customised etching available	



PBP-044/C1

PRODUCT CODE 51874

Weight	0.90 kg (4 buttons installed)	
Dimensions (WxHxD)	290 mm x 130 mm (buttons protrude 25.5 mm from front of panel)	
Orientation	Horizontal	
Buttons	1 green + 3 red, mushroom push-lock, turn-reset switches	
Etching	Student Call Fire Evacuation Duress Emergency Lockdown Customised etching available	



PBP-044/C5

PRODUCT CODE 51926

Weight	0.90 kg (4 buttons installed)	
Dimensions (WxHxD)	290 mm x 130 mm (buttons protrude 25.5 mm from front of panel)	
Orientation	Horizontal	
Buttons	4 red, mushroom push-lock, turn-reset switches	
Etching	No panel etching Customised etching available	