



INTERCOM TERMINAL VSL-350Q+

PRODUCT CODE 51699

FEATURES

- IP audio intercom terminal
- Standard PoE powered (IEEE 802.3af)
- Two configurable relays that can control lights, gate/door access etc.
- Tamper detection and attempted device removal notification
- Automated testing of speaker and microphone
- Anti-ligature speaker design to prevent self harm in security environments
- Water and vandal resistant

SPECIFICATIONS

Speaker	1 x 4 Ω, 1 W RMS (power rating)
Speaker Amplifier	50 Hz - 7 kHz (output circuit frequency response -3 dB), 2.5 W
Max. Acoustic Output	88 dB SPL @ 1 m, 0 dBFS 1 kHz (non-clipped) sine wave signal
Speaker Hole Size	193 holes x 1.6 mm (0.06 in) diameter, anti-ligature design
Microphone	Electret condenser, omnidirectional, sensitivity -56 dB 50 Hz - 7 kHz (input circuit frequency response ±3 dB mic)
Microphone Hole Size	1 hole x 2.5 mm (0.01 in) diameter
LED	1 x 5 mm (0.19 in), Green
Audio Streaming Bandwidth	128 kb/s one way, 256 kb/s both ways
Auxiliary Functions	Relay contacts (2 x NO/NC), 30 V d.c/2 A Tamper detection and attempted device removal notification
Power Input	IEEE 802.3af Power over Ethernet (PoE) (cannot be locally powered)
Power Consumption	4.5 W max. (1.6 W standby) PoE Class 2 (3.84-6.49) W
Operating Temperature	(0 - 55) °C (32 - 131) °F
Operating Humidity	(10 - 95) % relative humidity (non-condensing)
Cabling	4 pair UTP CAT-5/6, multi-strand, 24 AWG, 100 m (328 ft) max.
Dimensions (WxHxD)	125 mm x 180 mm x 58 mm (4.92 in x 7.08 in x 2.28 in) 67 mm (2.64 in) min. mounted depth
Weight	0.59 kg (1.30 lb)
Material	316 stainless steel, 2 mm (0.08 in)
Finishes	Linish
Environment	Indoor and outdoor
Vandal Resistant	Yes; strong front panel, speaker and microphone aperture vandal protected
Mounting Options	Flush mount backbox (FWE-14), surface mount backbox (SWE-6/SWE-4SS), rainhood (SRH-1)
Mounting Holes	4 holes x 4.5 mm (0.18 in) diameter
Fixings	4 x M4 security torx screws (included with purchase of backbox)

OPTIONS

Customisation	Etching
----------------------	---------