



INTERCOM TERMINAL VSL-371W

PRODUCT CODE 51339

FEATURES

- IP audio intercom terminal
- Tamper detection and attempted device removal notification
- Automated testing of speaker and microphone
- 316 type Stainless Steel
- Water and vandal resistant

SPECIFICATIONS

Speaker	1 x 4 Ω, 3 W RMS (power rating)
Speaker Amplifier	50 Hz - 7 kHz (output circuit frequency response -3dB), 2.5 W
Max. Acoustic Output	85 dB SPL @ 1 m, 0 dBFS 1 kHz (non-clipped) sine wave signal
Speaker Hole Size	58 x 3 – 6 mm Ø holes
Microphone	Electret condenser, omnidirectional, sensitivity -56 dB 50 Hz - 7 kHz (input circuit frequency response ±3 dB mic)
Microphone Hole Size	1 x "koala nose", 6 x 10 mm
Audio Bandwidth	50 Hz – 7 kHz, -3 dB
Control Buttons	1 x piezo switch, red, 19 mm
Auxiliary Functions	Relay contacts (2 x NO/NC), 30 V d.c./2 A - Optional module Tamper detection and attempted device removal notification Automated testing of speaker and microphone
Power Input	(12-36) V d.c IEEE.802.3af (PoE) - Optional Module JPoE (24 v.d.c.) via optional JPP-6/12/240 - PoEA-1/6
Power Consumption	4.5 W max. (1.6 W standby) PoE Class 2 (3.84-6.49) W
Operating Temperature	(0 - 50) °C
Operating Humidity	(10 – 95) % non-condensing
Cabling	4 pair UTP CAT-5/6, multi-strand, 24 AWG, max. 100 m 0.75mm ² Figure 8 (Power feed if not JPoE)
Dimensions (WxHxD)	75 mm x 261 mm x 92 mm 95 mm min. mounted depth
Weight	0.65 kg
Material	316 stainless steel (2 mm)
Finishes	Linish
Environment	Indoor and outdoor
Vandal Resistant	Yes; strong front panel, speaker and microphone aperture vandal protected
Mounting Options	Flush mount (cut out and tap), rainhood (SRH-4)
Mounting Holes	6 x 5 mm Ø screw holes
Fixings	6 x M4 security torx screws (included with purchase of backbox)