ENTRANCE STATION VES-741

PRODUCT CODE 51423

FEATURES

- Attractive slimline design
- Wide angle camera
- Two configurable relays that can control lights, gate/door access etc.
- Insect resistant microphone/speaker
- 316 type stainless steel construction
- Weather resistant, with optional rain cover
- Call one master/monitor station

SPECIFICATIONS

Camera	Type: 1/3" CCD image sensor, LED illumination Resolution: 520 TVL Sensitivity: 0.1 lux Functions: AES, AGC, BLC, AWB, Lens: f = 2.5 mm, f 2.0 Viewing angle: 75° V, 105° H
Speaker	1 x 4 Ω 1 W
Speaker Amplifier	50 Hz – 7 kHz (output circuit frequency response -3 dB), 2.5 W
Max. Acoustic Output	88 dBSPL @ 1 m, 0 dBFS 1 kHz (non-clipped) sine wave signal
Microphone	Electret condenser, omnidirectional, sensitivity -56 dB 50 Hz – 7 kHz (input circuit frequency response ±3 dB mic)
Audio Streaming Bandwidth	256 kb/s both ways
Control Buttons	1 x piezo switch, black, 19 mm (0.75 in)
Auxiliary Functions	Relay contacts (2 x NO/NC), power saving modes, light sensor
Power Input	IEEE 802.3af Power over Ethernet (PoE) Auxiliary power input: (12 - 32) V d.c.
Power Consumption	8.5 W max. (2.0 W standby) (VES-741)
Operating Temperature	(0 - 50) °C (32 - 122) °F
Operating Humidity	(20 - 90) % relative humidity (non-condensing)
Cabling	LAN: 4 pair UTP CAT-5/6, multi-strand, 24 AWG, 100 m (328 ft) max. Power: Figure 8, 0.75 mm² (0.0012 in²) conductors
Dimensions (WxHxD)	130 mm x 290 mm x 45 mm (5.12 in x 11.42 in x 1.8 in)
Weight	1.6 kg (3.5 lb)
Material	316 stainless steel (3 mm / 0.12 in)
IP rating	IP66 tested according to AS 60529:2004 (using the mounting options specified)
Finishes	Bead blasted, electro-polished
Environment	Indoor and outdoor use
Vandal Resistant	Yes
Mounting Options	Flush mount backbox (FWE-1), surface mount backbox (SWE-9SS), rainhood (SRH-2), Pole Mount Bracket (PMB-410)
Fixings	6 x M4 security torx screws (included with purchase of backbox)