CONTROLLER

JSC-5L | 51814

Features

IP controller, large, more than 80 endpoints supported
Includes JCCP server software for intercom devices to makeand receive calls
Supports high definition audio
SATA hard drive (Enterprise)
Segregated air-flow design for optimal unit cooling
Redundant, hot swappable power supply

Package Contents

JSC-5L controller
Power cable (IEC 60320) C13 x 2
Rack mount rails
JELinux and JCCP Software

Optional Packages

Software

Intercom Report Server
High Level Interface
Event Controller
Voice Annunciator
High Availablility Package
DAR
SIP Proxy

Hardware

Redundant HDDs—RAID 1

Specifications

Endpoints Supported	2000*
RAM	8GB 3200MHz DDR4 ECC Unbuffered DIMM 1Rx8 RAM
Storage	2TB 3.5“ SATA 6Gbps 7200RPM 128MB Cache Hard Drive
Chipset	Intel® C252
CPU	Intel Xeon E-2336 Processor, 6-Core 2.90GHz 12MB cache 65W
Indicators	LAN1 Link & Activity, LAN2 Link & Activity, Power, HDD, System Status
Dimensions (WxHxD)	438 mm x 87 mm x 557.2 mm (17.24 in x 3.42 in x 21.94 in)
Weight	12 kg (26.45 lb)
Material	Steel, powder coated black
Mouning Options	2RU rack mounting, 580mm min rack depth
Power Input	(100 – 240) V a.c., (10 – 3.5) A a.c. 50-60Hz, IEC 60320 C14
Power Consumption	Acbel 800W redundant PS module
External Connections	2 x LAN (1 GB), 6 x USB 3.0, VGA, RS232, IPMI
Operating Temperature	(5 - 35) °C (41 - 95) °F
Operating Humidity	(8 - 90) % (non-condensing)
Non-operating Temperature	(-40 – +60) °C (-40 - 140) °F
Non-operating Humidity	(5 – 95) % (non condensing)

* Dependent on server configuration and network bandwidth