PC MASTER STATION

PCC-4650WIN | 52257

Features

4th generation IP Master Station for complete call and PA functionality

Complete call handling functions

- Call queue display
- Call notification display
- Call originate
- Call answer/end/hold/forward
- Group calling
- Call monitoring
- Central control location for duress/concierge calls

Complete public address functionality

- Make live and pre-recorded announcements
- Broadcast tones, bells & alarms
- Visual display of PA zones (unlimited number of zones depending on controller)
- Selection and playback of recorded announcements
- Send text messages to video monitor stations

Diagnostics and reporting

Alarm notifications including device state

Incoming call & connected call video from select video intercom devices

Video from third party CCTV cameras

Send text message notifications to Jacques Video Monitor Stations

- Map, grid and database views
- Upload multiple site maps to suit application/site
- Customisable layout/functions to suit application requirements

Customisation

Customisable Graphical User Interface (J650UI)

Package Contents

Mini-PC

Screen, keyboard & mouse

IMC-4000 IP Master Console

Specifications

Screen	Size: 24 in Resolution: 1920 x 1080 LED LCD Contrast ratio: 5000:1 Brightness: 250 cd/m² Viewing angle: 178° H, 178° V
Speaker	1 x 4 Ω, 3 W RMS (power rating)
Speaker Amplifier	200 Hz - 7.0 kHz (output circuit frequency response -3 dB)
Max. Acoustic Output	88 dBSPL @ 1 m (3.28 ft), 0 dBFS 2.5 kHz (non-clipped) sine wave signal
Microphone	Microphone type: Gooseneck Output type: Uni-directional electret condenser Frequency response: 50 Hz – 18 kHz Sensitivity: -70 dB ± 3 dB @ 1 kHz
Audio Streaming Bandwidth	256 kb/s both ways
Mini PC	Intel NUC7i5BNH, 500GB HDD, 4GB RAM
Power Consumption	18 W max. (PCC-4650WIN) 25.5 W max, 3.6 W standby (IMC-4000) 65 W max (Mini-PC)
Power Input	(100 – 240) V a.c. power cords/adapters included, 2 power outlets required
Control Buttons	Stainless steel mechanical push-to-talk and volume buttons (IMC-4000)
Auxiliary Functions	Relay contacts (1 x NO/NC) max. 2 A @ 24 V d.c.
Operating Temperature	0 - 40 °C (32 - 104) °F
Operating Humidity	(20 - 80) % relative humidity (non-condensing) (PCC-4650WIN) (10 - 90) % relative humidity (non-condensing) (IMC-4000)
Cabling	UTP CAT-5/5e/6, multi-strand 0.75 mm² (0.00116 in²), 100 m (328 ft) max.
Dimensions	568 mm x 418 mm x 191 mm (PCC-4650WIN) 130 mm x 71.5 mm x 150 mm (5.12 in x 2.85 in x 5.91 in) IMC-4000 115 mm x 111 m x 32 mm (4.52 in x 0.04 in x 1.26 in) Mini-PC
Weight	5 kg (11.02 lb) PCC-4650WIN 1.2 kg (2.65 lb) IMC-4000 0.7 kg (1.54 lb) Mini PC
Environment	Indoor use only
Mounting Options	VESA desk stand (Mini PC) Desk mount (IMC-4000)
Compliance	CAN ICES-3(B)/NMB-3(B)