

ACCESSORIES

5 SERIES MOUNTING

Specifications

Suitable for	VSL-x5x series
Dimensions (WxHxD)	98 mm x 142 mm x 57 mm (3.85 in x 5.59 in x 2.24 in)
Weight	0.5 kg (1.10 lb)
Material	Zincanneal steel
Finishes	Zinc plated and passivated
Environment	Indoor use only
Intercom Mounting Holes	4 x M4 threaded hole
Intercom Fixings	4 x M4 security torx screws (included with purchase of backbox)
Cable Entry	5 holes x 28 mm (1.1 in) diameter centred top, bottom, right, left and rear

FWE-14 | 51274



Suitable for	VSL-x5x series
Dimensions (WxHxD)	263.3 mm x 129.5 mm x 66.6 mm (10.36 in x 5.09 in x 2.62 in)
Weight	0.6 kg (1.32 lb)
Material	316 stainless steel
Finishes	Linish
Environment	Indoor and outdoor
Intercom Mounting Holes	4 x M4 threaded hole
Intercom Fixings	4 x M4 security torx screws (included with purchase of backbox)
Cable Entry	1 x 100 mm x 64 mm (3.94 in x 2.51 in) rectangular rear cut out

SWE-17/C1 | 60721



Suitable for	VSL-x5x series
Dimensions (WxHxD)	125.5 mm x 180.5 mm x 60 mm (4.94 in x 7.10 in x 2.36 in)
Weight	0.9 kg (1.98 lb)
Material	316 stainless steel
Finishes	Linish
Environment	Indoor and outdoor
Intercom Mounting Holes	10 x M4 threaded holes
Intercom Fixings	10 x M4 security torx screws (included with purchase of backbox)
Cable Entry	1 hole x 25 mm (1 in) diameter centre of rear

SWE-4SS | 60714



Suitable for	VSL-x5xW+ series
Dimensions (WxHxD)	156 mm x 201 mm x 135 mm (6.14 in x 7.91 in x 5.31 in)
Weight	1.3 kg (2.86 lb)
Material	316 stainless steel
Finishes	Linish
Environment	Outdoor
Intercom Mounting Holes	4 x M4 threaded holes
Intercom Fixings	4 x M4 security torx screws (included with purchase of backbox)

SRH-1 | 50213



Suitable for	VSL-x5x series
Dimensions (WxHxD)	125.5 mm x 180.5 mm x 60 mm (4.94 in x 7.10 in x 2.36 in)
Weight	0.9 kg (1.98 lb)
Material	Zincanneal steel
Finishes	Powder coated, APO ripple grey
Environment	Indoor and outdoor
Intercom Mounting Holes	4 x M4 threaded holes
Intercom Fixings	4 x M4 security torx screws (included with purchase of backbox)
Cable Entry	1 hole x 25 mm (1 in) diameter centre of rear

SWE-6 | 60712

