



HELP POINT UNIT HPU-5E2+/HPU-5E2-i+

PRODUCT CODE 51687, 51688

FEATURES

Highly visible, solid, vandal resistant unit, designed with public safety in mind
 Simple 1 or 2 button operation, emergency or emergency & information
 Environmentally sealed
 One-touch operation with hands-free communication, once call is established
 Standard PoE powered (IEEE 802.3af)
 Tamper detection and attempted device removal notification
 Automated testing of speaker and microphone
 Vandal and water resistant piezo electric call button(s)
 Anti-graffiti coating to protect against vandalism
 Two configurable relays

CUSTOMISATION

Custom artwork for shell, control surfaces and label

SPECIFICATIONS

Speaker	1 x 4 Ω 3 W RMS (power rating)
Speaker Amplifier	50 Hz – 7 kHz (output circuit frequency response -3 dB), 2.5 W
Max. Acoustic Output	88 dB SPL @ 1 m, 0 dBFS 1 kHz (non-clipped) sine wave signal
Speaker Hole Size	42 x 4 – 7 mm Ø holes
Microphone	Electret condenser, omnidirectional, sensitivity -56 dB 50 Hz – 7 kHz (input circuit frequency response ±3 dB mic)
Microphone Hole Size	6 x 3 & 5 mm Ø holes
Audio Streaming Bandwidth	128 kb/s one way, 256 kb/s both ways
Control Buttons	1 x piezo switch, red, 28 mm (HPU-5E2+) 2 x piezo switches, 1 x red, 1 x blue, 28 mm (HPU-5E2-i+)
Auxiliary Functions	Relay contacts (2 x NO/NC), 30 V d.c./2 A Tamper detection and attempted device removal notification Automated testing of speaker and microphone
Power Input	IEEE 802.3af Power over Ethernet (PoE)
Power Consumption	4.5 W max. (1.6 W standby) PoE Class 2 (3.84-6.49) W
Operating Temperature	(0 - 50)°C
Operating Humidity	(10 - 95) % relative humidity (non-condensing)
Cabling	4 pair UTP CAT-5, multi-strand, 24 AWG, max. 100 m
Dimensions (WxHxD)	320 mm x 420 mm x 120 mm
Weight	7.8 kg
Material	Front shell: 5 mm die cast aluminium Front control panel: 316 type stainless steel (3 mm) Back: 316 type stainless steel (3 mm)
Finishes	Dulux orange powder coated, with a clear anti-graffiti lacquer
Environment	Indoor and outdoor use
Vandal Resistant	Yes
Mounting Options	Wall mount (WMP-5), bollard (BOL-3xx)
Mounting Holes	6 x M6 stainless tapped standoffs (HPU to rear panel)
Fixings	6 x M6 security torx screws, 6 x nylon washers (HPU to rear panel)