



VMI-155M

VMI STANDALONE MASTER STATION VMI-155M

PRODUCT CODE 50634

FEATURES

- Standalone intercom system
- Master station supports up to 4 slave intercoms
- Balanced line out for recording
- Vandal resistant design
- Dry relay contact output for door/gate control

CUSTOMISATION

- Intercom face etching

SPECIFICATIONS

| | |
|------------------------------|--|
| Speaker | 4 Ω, 3 W RMS (power rating) |
| Speaker Amplifier | 60 Hz to 12 kHz, 1 W RMS |
| Max. Acoustic Output | 88 dB SPL @ 1 m, 1 kHz (non-clipped) sine wave signal |
| Speaker Hole Size | 42 x 4 – 7 mm Ø holes |
| Microphone | Electret condenser, omnidirectional, sensitivity -55 dB 160 Hz – 16 kHz (input circuit frequency response ±3 dB) |
| Microphone Hole Size | 1 x 2.5 mm Ø hole |
| Audio Bandwidth | 160 Hz - 12 kHz |
| Control Buttons | 4 x stainless steel call push buttons, 19 mm 1 x stainless steel push-to-talk button, 19 mm |
| Auxiliary Functions | Electronically balanced signal, -4 dBu nominal |
| Power Input | (12 – 32) V d.c. (24 V nominal) |
| Power Consumption | 5 W max. |
| Operating Temperature | (0 – 50) °C |
| Operating Humidity | (10 – 95) % relative humidity (non-condensing) |
| Cabling | Audio & Data: UTP CAT-5/6, multi-strand, 24 AWG Recording Audio: single pair screened cable Power: Figure 8, 0.75 mm ² multi-strand |
| Configuration | 1-4 Jacques VSL-251 intercom terminals (daisy chained) |
| Dimensions (WxHxD) | 130 mm x 290 mm x 45 mm |
| Weight | 1.0 kg |
| Material | 316 stainless steel (2 mm) |
| Finishes | Linish |
| Environment | Indoor and outdoor |
| Vandal Resistant | Yes |
| Mounting Options | Flush mount backbox (FWE-1), surface mount backbox (SWE-1/SWE-9SS) |
| Mounting Holes | 6 x 5 mm Ø screw holes |
| Fixings | 6 x M4 security torx screws |