



## INTERCOM TERMINAL VSL-74K

PRODUCT CODE 51459

### FEATURES

- IP device used for voice control and communications
- 12 button keypad
- Standard PoE powered (IEEE 802.3af)
- Marine grade 316 type stainless steel face plate
- Two configurable dry contact relays (control lights, gate/door access)
- Water bead and insect nest deterring microphone aperture
- Vandal resistant stainless steel front panel with call instruction etching

### SPECIFICATIONS

<b>Microphone</b>	Electret condenser, omnidirectional, sensitivity -56 dB
<b>Speaker</b>	1 x 4Ω, 1W RMS (power rating)
<b>Speaker Amplifier</b>	50Hz - 7kHz (output circuit frequency response -3dB), 2.5 W
<b>Configuration</b>	Unlimited* number of VSL-74K
<b>Control Buttons</b>	12 button keypad (0-9, * and #)
<b>Dimensions (WxHxD)</b>	130mm x 290mm x 53mm
<b>Weight</b>	1.4kg
<b>Environment</b>	Internal and external use
<b>Material</b>	316 stainless steel front panel
<b>Finishes</b>	Linished and bead blasted
<b>Vandal Resistant</b>	Yes
<b>Mounting Options</b>	Flush mount backbox (FWE-1), surface mount backbox - powder coated (SWE-1) or stainless steel (SWE-9SS)
<b>Fixings</b>	6 x M4 security torx screws
<b>Power Input</b>	IEEE.802.3af Power over Ethernet (PoE) Auxiliary power input: (12 - 32) V d.c.
<b>Power Consumption</b>	8.5 W max (2.0 W standby)
<b>Cabling: Power &amp; Ethernet</b>	4 pair UTP CAT-5/6, multi-strand, 24 AWG - max 100m
<b>Audio Streaming Bandwidth</b>	200 Hz - 7 kHz +/- 3 dB (voice)
<b>Max. Acoustic Output</b>	88 dB SPL @ 1m, 0dBFS 1kHz (non-clipped) sine wave signal
<b>Auxiliary Functions</b>	Relay contacts (2 x NO/NC)
<b>Operating Temperature</b>	0 - 50°C
<b>Operating Humidity</b>	20 - 90% relative humidity (non-condensing)

\*Dependent on server configuration and network bandwidth